



Horizontal Mount Bi-Color Lights

1-mile Certified A-16 for replacement use only - Patent No. 4,500,947

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Brass or Stainless Steel, Polymer Base Material:

Finish: Chrome Plated or Polished

Dimensions: Length: 4-1/4", Width: 2-3/8", Height: 1-1/2"

Screw Size:

Contacts: **Gold Plated**

Voltage: 12V (Bulb Included)

Wattage: 10 watts Amperage: .80 amps



Fig. 0904

Finish Retail Pkg. Chrome 0904DP0CHR Polished SS 0904DP0STS







1-mile Certified A-16 for replacement use only

Use on Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Zinc Alloy Finish: Chrome Plated

Dimensions: Length: 6-3/4", Width: 3-7/8",

Height: 3-1/4"

3/4" Flag Socket: Screw Size: #8

12V (Bulb Included) Voltage:

Wattage: 10 watts Amperage: .80 amps

Flag Staff Socket Features:



Fig. 1218

Finish Retail Pkg. Chrome 1218DP0CHR





NOTE: The above light scan also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

Fig. 0904:

Bulbs: 0071DP0CLR. Lens Set: 0296DP0LNS. Base with Socket Assembly: 0107.

Fig. 1218:

Bulbs: 0071DP0CLR. Lens Set: 0259DPALNS. Socket Assembly: 1218DP099A.

Spare Parts Information





Fig. 0296DP0LNS

